





GJSJV Simplex Armoured Round Cable

Indoor

Cable structure:



Description:

GJSJV Simplex Armoured Round Cable use 600um & 900um tight buffer fiber, steel tube protect, reinforcing steel-wire braiding (Kevlar/aramid yarn), flame-retardant jacket. High indentation strength, high tensile strength, gopher protected, small diameter, flexibility and easy bend.

Features:

- 0.6mm or 0.9mm tight buffer fiber .
- Hight strength kevlar yarn member.
- Steel armored flexible tube, increase the cable's twist resistance.
- · Small cable volume, and light weight.

Application:

- Adopted to indoor distribution .
- As pigtail of communication equipment .
- Suitable for communication equipment served.
- Can be installed conveniently and perated simply.

Technical parameters

Cable type	OD (mm)	Nominal Weight (kg/km)	Tensile Strength(N)		Crush Resistance (N/100MM)		Bending Radius(mm)	
			Short-term	Long-term	Short-term	Long-term	Dynamic	Static
GJSJV-1Xn	1.8±0.2	16.0	400	200	2000	1000	20D	15D
GJSJV-1Xn	2.8±0.2	18.5	400	200	2000	1000	20D	15D
${\sf Storage/Working\ temperature}({\mathbb C})$			-20~+60					

Note: Xn is fiber optic model and D is the diameter of optical cable.

Packing and Reel Length

- ★.Standard wooden drum with protection.
- ★.Standard reel length: 2/3 km/reel, other length is also available.